



- 1.CABLE:UL2725,28AWG(7/0.12mm)×1PAIRS  
+24AWG(7/0.2mm)×2C,TIN COPPER  
INSULATOR:P.P FOR 28AWG&PVC 24AWG  
SHIELD:AL-FOIL+DRAIN WIRE+BRAID  
JACKET:PVC,COLOR:GREY,Ø.D:4.8mm±0.2mm
- 2.CONNECTOR:1 PCS USB A SOLDER TYPE MALE  
COLOR:WHITE COLOR  
SHELL:NICKEL PLATED
- 3.CONNECTOR:1 PCS USB B SOLDER TYPE MALE  
COLOR:WHITE COLOR  
SHELL:NICKEL PLATED
- 4.HOOD:MOULDED GREY COLOR
- 5.Fulfill ROHS Guideline
- 6.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

### WIRE LIST

P1		P2	
USB A MALE	WIRE COLOR	USB B MALE	AWG
1	RED	1	24AWG
2	WHITE	2	1 PAIRS (28AWG)
3	GREEN	3	
4	BLACK	4	24AWG
SHELL	DRAIN	SHELL	

PART NO	CAB-USBAB-1.0	SHEET NO	1	THIRD ANGLE PROJECTION			
TITLE:USB A MALE TO USB B MALE L:1.0M,UL2725 CABLE,GREY COLOR				SCALE	N.T.S	DRAWN BY & DATE	
				SIZE	A4	CHECKED BY & DATE	
DWN NO				UNIT		APPROVED BY & DATE	
				<input checked="" type="checkbox"/> mm	<input type="checkbox"/> INCH		

