



|                        |               |
|------------------------|---------------|
| <b>Symbol:</b>         | FLCC-40/30    |
| <b>Product groups:</b> | Ribbon Cables |

## Product specifications

|                                  |                                |
|----------------------------------|--------------------------------|
| <b>Type of wire:</b>             | ribbon                         |
| <b>Cable structure:</b>          | 40x28AWG                       |
| <b>Tape pitch:</b>               | 1.27mm                         |
| <b>Core structure:</b>           | stranded                       |
| <b>Kind of core:</b>             | Cu, tinned                     |
| <b>Number of cores:</b>          | 40                             |
| <b>Core diameter:</b>            | 28AWG                          |
| <b>Core marking:</b>             | colours with colour repetition |
| <b>Shield structure:</b>         | unshielded                     |
| <b>Wire insulation material:</b> | PVC                            |

|                               |            |
|-------------------------------|------------|
| <b>Rated voltage:</b>         | 0.3kV      |
| <b>A dimension:</b>           | 50.8mm     |
| <b>B dimension:</b>           | 49.53mm    |
| <b>Package contents:</b>      | 30.5m      |
| <b>Earth core:</b>            | none       |
| <b>Operating temperature:</b> | -20...80°C |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 2.628 kg |
|----------------------|----------|