


## Product card FLC-64/30-E

---



|                        |               |
|------------------------|---------------|
| <b>Symbol:</b>         | FLC-64/30-E   |
| <b>Product groups:</b> | Ribbon Cables |

### Product specifications

|                                  |            |
|----------------------------------|------------|
| <b>Type of wire:</b>             | ribbon     |
| <b>Tape pitch:</b>               | 1.27mm     |
| <b>Core structure:</b>           | stranded   |
| <b>Kind of core:</b>             | Cu, tinned |
| <b>Number of cores:</b>          | 64         |
| <b>Core diameter:</b>            | 28AWG      |
| <b>Shield structure:</b>         | unshielded |
| <b>Wire insulation material:</b> | PVC        |
| <b>Insulation colour:</b>        | grey       |

|                               |               |
|-------------------------------|---------------|
| <b>Operating temperature:</b> | -20...105°C   |
| <b>Rated voltage:</b>         | 0.3kV         |
| <b>Package contents:</b>      | 30.5m         |
| <b>Cable structure:</b>       | 64x28AWG      |
| <b>Conform to the norm:</b>   | UL 2651, VW-1 |

## **Additional information**

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 3.609 kg |
|----------------------|----------|